



INDUSTRIAL GARBAGE BAGS CHARACTERISTICS

- Excellent strength and puncture resistance eliminates the need for double bagging
- Less harmful for the environment and are certified UL Ecologo by a well recognized Canadian third party certification body
- Material: Recycled Material
- Type: Open Top



Model No.	Strength	Dim. L" x W"	Qty/Box	Thickness mils
BLACK				
JM669	Utility	22 x 20	500	0.64
JM670	Utility	24 x 22	500	0.64
JM671	Utility	22 x 24	500	0.64
JM672	Regular	36 x 26	250	0.7
JM673	Regular	38 x 30	250	0.7
JM674	Regular	50 x 35	200	0.75
JM675	Strong	36 x 26	200	0.9
JM676	Strong	38 x 30	200	0.9
JM677	Strong	50 x 35	125	0.9
JM678	Strong	48 x 42	125	0.9
JM679	X-Strong	36 x 26	125	1.2
JM680	X-Strong	38 x 30	125	1.2
JP572	X-Strong	50 x 35	100	1.2
JP573	X-Strong	48 x 42	75	1.2
JO224	X-Strong	50 x 50	50	1.5
JM683	2X Strong	50 x 35	75	1.9
JO107	3X Strong	38 x 30	50	3.0
JM684	3X Strong	50 x 35	50	3.0
WHITE				
JM685	Utility	22 x 20	500	0.64
JM686	Utility	24 x 22	500	0.64
CLEAR				
JM687	Utility	22 x 20	500	0.64
JM688	Utility	24 x 22	500	0.64
JM689	Strong	36 x 26	200	0.9
JM690	Strong	38 x 30	200	0.9
JM691	Strong	50 x 35	125	0.9
JM692	Strong	48 x 42	125	0.9
JM693	X-Strong	36 x 26	125	1.2
JM694	X-Strong	38 x 30	125	1.2
JP574	X-Strong	50 x 35	100	1.2
JP575	X-Strong	48 x 42	75	1.2
JO156	3X Strong	50 x 35	50	3.0
JO225	X-Strong	50 x 50	50	1.5



RMP Maintenance Products®

22555 Aut. Transcanadienne, Senneville, Quebec H9X 5X5

Phone: (866) 457-1163 Fax: (866) 457-1164

rmpmaintenance.com

info@rmpmaintenance.com